

Composición**Ancho****Largo de rollos****Peso**

100% Poliéster FR

300 cm ± 2%

± 35 mts

280 gr/m² ± 5%

4-5

EN ISO 105-B02:2014

Método 2 escala 1-8; 8 mejor valor

> 80.000 ciclos (A)

Solidez a la luz**Resistencia a la
abrasión**

UNE EN ISO 12947-2:1998/AC:2006

Escala A-C; A mejor valor

3-4 (C)

EN ISO 12945-2:2000

Escala A-D; A mejor valor

Pilling**Encogimiento**

Urdimbre: 1% · Trama: 1%

UE: UNE EN 13773:2003 (C-1)

F: NF P92-507:1995 (M-1)

Consultar:

A: B-1 DIN 4102 (B1)

I: C-1 UNI 9176:1998 (C-1)

USA: NFPA 701

**Certificados
ignifugos****Igualdad color**

El color puede variar de una partida a otra

Material**Width****Roll length****Weight**

100% Polyester FR

300 cm ± 2%

± 35 mts

280 gr/m² ± 5%

4-5

EN ISO 105-B02:2014

Method 2 scale 1-8; 8 best value

> 80.000 cycles (A)

Light fastness**Abrasion
resistance**

UNE EN ISO 12947-2:1998/AC:2006

Scale A-C; A best value

3-4 (C)

EN ISO 12945-2:2000

Scale A-D; A best value

Pilling**Shrinkage**

Warp: 1% · Weft: 1%

EU: UNE EN 13773:2003 (C-1)

F: NF P92-507:1995 (M-1)

Inquire:

A: B-1 DIN 4102 (B1)

I: C-1 UNI 9176:1998 (C-1)

USA: NFPA 701

**Fire resistance
certifications****Colour matching**

Colour may vary from batch to another

MADE IN
BARCELONA